Polysafe Standard PUR

Polysafe Standard PUR is a heavy-duty safety flooring with a traditional decoration. Ideal in hygiene critical locations subjected to contaminant spillages, Standard provides sustainable slip resistance and continued underfoot protection. Featuring a Polysafe PUR maintenance enhancement for improved cleanability, the range is used in water spillage areas such as food preparation areas, bar serveries, clinics, laundry and sluice rooms, washrooms, WCs, laboratories, classrooms and many institutional applications. For continually wet areas such as showers, please refer to our Polysafe Hydro, Hydro Evolve or Quattro ranges.



Gauge	ISO 24346 (EN 428)	2.0mm 2.5mm
Sheet Size	ISO 24341 (EN 426)	2.0mm : 2m x 20m = 40m ² 2.5mm : 2m x 20m = 40m ²
Total Weight	ISO 23997 (EN 430)	2.0mm : 2430g/m² 2.5mm : 3100g/m²
General Performance	EN 13845 ASTM F1303	Conforms Conforms
Use Area	ISO 10874 (EN 685)	
	EN 13845	ESf
Enhanced Slip Resistance	AS 4586	R10
	DIN 51130	R10
	RRL Pendulum Test	≥36 (wet test - 4S Rubber/Slider 96)
	Surface Roughness	Rz ≥20µm
Enhanced Slip Resistance	ASTM D2047 The wet slip resistance across all Poly	
Enhanced Slip Resistance Abrasion Resistance	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence	SCOF ≥0.8 ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding slip 50,000 cycles
, , , , , , , , , , , , , , , , , , ,	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor.	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding sli
Abrasion Resistance	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding sli 50,000 cycles
, , , , , , , , , , , , , , , , , , ,	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845 EN 13501-1	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding sli 50,000 cycles Class Bfl-S1
Abrasion Resistance	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845 EN 13501-1 ASTM E648	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding slij 50,000 cycles Class Bfl-S1 Class 1
Abrasion Resistance	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845 EN 13501-1 ASTM E648 AS ISO 9239-1	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding slip 50,000 cycles Class Bfl-S1 Class 1 >8.0kW/m²
Abrasion Resistance Reaction to Fire	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845 EN 13501-1 ASTM E648 AS ISO 9239-1 CAN/ULC S102.2	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding slij 50,000 cycles Class Bfl-S1 Class 1 >8.0kW/m² FSV < 300; SDV < 500
Abrasion Resistance Reaction to Fire Static Electrical Propensity	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845 EN 13501-1 ASTM E648 AS ISO 9239-1 CAN/ULC S102.2 EN 1815	ysafe products is sustainable throughout the guaranteecto HSE Guidelines. For further clarification regarding slip 50,000 cycles Class Bfi-S1 Class 1 >8.0kW/m² FSV < 300; SDV < 500 ≤2.0kV Classified as 'antistatic'
Abrasion Resistance Reaction to Fire	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845 EN 13501-1 ASTM E648 AS ISO 9239-1 CAN/ULC S102.2 EN 1815 Indoor Air Comfort GOLD	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding slip 50,000 cycles Class BfI-S1 Class 1 >8.0kW/m² FSV < 300; SDV < 500 ≤2.0kV Classified as 'antistatic' Eurofins certified product
Abrasion Resistance Reaction to Fire Static Electrical Propensity	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845 EN 13501-1 ASTM E648 AS ISO 9239-1 CAN/ULC S102.2 EN 1815 Indoor Air Comfort GOLD AgBB/ABG	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding slij 50,000 cycles Class BfI-S1 Class 1 >8.0kW/m² FSV < 300; SDV < 500 ≤2.0kV Classified as 'antistatic' Eurofins certified product Pass
Abrasion Resistance Reaction to Fire Static Electrical Propensity	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845 EN 13501-1 ASTM E648 AS ISO 9239-1 CAN/ULC S102.2 EN 1815 Indoor Air Comfort GOLD AGBB/ABG FloorScore	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding slij 50,000 cycles Class Bfl-S1 Class 1 >8.0kW/m² FSV < 300; SDV < 500 ≤2.0kV Classified as 'antistatic' Eurofins certified product Pass Certified
Abrasion Resistance Reaction to Fire Static Electrical Propensity VOC Emissions	ASTM D2047 The wet slip resistance across all Poly of the product, with strict adherence resistance, consult Polyflor. EN 13845 EN 13501-1 ASTM E648 AS ISO 9239-1 CAN/ULC S102.2 EN 1815 Indoor Air Comfort GOLD AgBB/ABG FloorScore Finnish M1 Classification	ysafe products is sustainable throughout the guaranteed to HSE Guidelines. For further clarification regarding slij 50,000 cycles Class Bfl-S1 Class 1 >8.0kW/m² FSV < 300; SDV < 500 ≤2.0kV Classified as 'antistatic' Eurofins certified product Pass Certified Certified

Environmentally Preferable Flooring - Polysafe Standard PUR achieves BRE Global A+ rating (ENP 472) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

Polysafe PUR - Polysafe Standard PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life



Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 7671912, or

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com. Decoration and shade may vary slightly from the samples shown.





































