

Polysafe™ QuickLay PUR

A loose lay safety flooring designed for adhesive free installation, Polysafe QuickLay can be laid over a variety of existing subfloors including new concrete substrates of up to 97% RH. Reduced subfloor preparation requirements & quicker installation makes Polysafe QuickLay the perfect solution for quick turnaround projects in areas where slip resistance is the priority. Typical areas include circulation areas & corridors, classrooms, hospital wards, clinics, nursing homes, washrooms, bar serveries, food preparation areas, canteens & institutional applications. For continually wet areas please refer to our Polysafe Hydro, Hydro Evolve or Quattro ranges.



	Gauge	ISO 24346/EN 428	2.2mm
	Roll Size	ISO 24341/EN 426	2m x 20m = 40m ²
	Total Weight	ISO 23997/EN 430	2700g/m ²
	General Performance	EN 13845 ASTM F1303	Conforms Conforms
	Use Area	ISO 10874/EN 685	
	Enhanced Slip Resistance	EN 13845 AS 4586 Appendix A AS 4586 Appendix D DIN 51130 RRL Pendulum Test Surface Roughness ASTM D2047	ESf P4 R11 R11 ≥45 (wet test - 4S Rubber/Slider 96) Rz ≥20µm SCOF >0.8 The wet slip resistance across all Polysafe products is sustainable throughout the guaranteed life of the product, with strict adherence to HSE Guidelines. For further clarification regarding slip resistance, consult Polyflor.
	Abrasion Resistance	EN 13845	50,000 cycles
	Reaction to Fire	EN 13501-1 ASTM E648 Australian BCA Spec C1.10-3 AS ISO 9239-1 CAN/ULC S 102.2	Class Bfl-S1 Class 1 Complies >8.0kW/m ² FSV <300; SDV <500
	Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
	VOC Emissions	Indoor Air Comfort GOLD AgBB/ABG FloorScore Finnish MI Classification	Eurofins certified product Pass Certified Certified
	Resistance to Chemicals	ISO 26987/EN 423	Good chemical resistance
	Castor Chair Abrasion	ISO 4918/EN 425	Suitable
	Acoustic Impact Sound Reduction	EN ISO 10140-3	10dB
	Residual Indentation	ISO 24343-1/EN 433	≤0.10mm
	Bacterial Resistance	ISO 846 Part C	Does not favour growth
Environmentally Preferable Flooring - Polysafe QuickLay PUR achieves BRE Global A+ rating (Generic) in the Green Guide to Specification in use areas such as education and healthcare. EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability			
Polysafe PUR - Polysafe QuickLay PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe QuickLay PUR should not have a polish applied.			
	Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.		
	Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com . The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com . Decoration and shade may vary slightly from the samples shown.		



Polyflor UK Sales Direct: +44 (0)161 767 1122 • Export Sales Direct: +44 (0)161 767 1913
Sample Requests: +44 (0)161 767 2551 • email: info@polyflor.com • www.polyflor.com

Polyflor Australia Tel: 1800 777 425 • email: sales@polyflor.com.au • www.polyflor.com.au
Polyflor New Zealand Tel: 0800 765 935 • email: sales@polyflor.co.nz • www.polyflor.co.nz

James Halstead
FLOORING