


The Native Collection PUR

PRODUCT SPECIFICATION

KEY FEATURES

- Replicate the native Australian wood.
- Withstand years of family living.
- Perfect residential applications.



 Tasmanian Blackbutt 3550

PRODUCT FORMAT	Standard	Result
Gauge	ISO 24346 (EN 428)	2.5mm
Wear Layer	ISO 24340 (EN 429)	0.55mm
Total Weight	ISO 23997 (EN 430)	4290g/m ²
Finish		PUR

PLANK SIZE	Size	Shades	Quantity per Box	Coverage per Box/Roll
Plank	184.2mm x 1524mm	8	12	3.37m ²

PERFORMANCE REQUIREMENTS	Standard	Result
General Performance	ISO 10582 (EN 649) ASTM F1700	Conforms Class III Type A+B
Use Area	ISO 10874 (EN 685)	23, 33, 42
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 Appendix D ASTM D2047	Class DS R10 R10 ≥0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T
Reaction to Fire	EN 13501-1 ASTM E662 ASTM E648 AS ISO 9239.1	Class Bfl-S1 <450 Pass Class 1 ≥ 8kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1 (EN 433) ASTM F970 ASTM F1914	≤0.05mm* ≤0.005" @ 750psi ≤0.005"

Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434) ASTM F2199	≤0.10% Pass
Flexibility	ASTM F137	1" - Pass
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

*Average test value from current production.

SUSTAINABILITY	Standard	Result
BRE Green Guide		A+ ENP 429
GreenTag		GreenRate™ Level A, LCA Rate™ Gold Plus
Specific EN 15804 EPD		Available
Recyclable		Recyclable via the Resiloop recycling scheme
Recycled Content		Up to 40%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001 SA 8000	Very good Approved factory

ACOUSTIC PERFORMANCE	Standard	Result
Impact Sound Reduction	ISO 10140-3	2dB
Sound Transmission Coefficient	ASTM E90/492	STC 55
Impact Insulation Class	ASTM E90/492	IIC 36

MAINTENANCE PERFORMANCE	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance

Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.



The Native Collection PUR

RANGE SHADES

8 Shades

Plank Size : 184.2 x 1524mm



3510 QUEENSLAND DRIFTWOOD



3540 JARRAH



3550 TASMANIAN BLACKBUTT



3554 BLACK CAVIAR

Plank Size : 184.2 x 1524mm



3615 ACACIA



3616 BRUNSWICK OAK



3617 MALVERN OAK



3618 RIMU

R10 All designs achieve R10, which is an ex-factory measure of slip resistance