

Polyclad

WALLCARE INFORMATION

Polyclad Plus PU • Polyclad Pro PU



The Polyclad range of wall and ceiling coverings are a homogeneous PVC vinyl sheet featuring a subtle marbled decoration with the protection of a polyurethane surface treatment. The following maintenance instructions are designed to minimise the cost factor, without compromising the long-term appearance of your wallcovering.

GENERAL ADVICE

- Regular cleaning is more beneficial to the wallcovering and more cost-effective than occasional heavy cleaning
- Always follow the Health & Safety guidance provided and dilute cleaners and detergents in accordance with the manufacturers' instructions
- Do not use strong kitchen detergents on vinyl surfaces
- For recommended products, see the Polyflor Approved Maintenance Products sheet

AFTER INSTALLATION IS COMPLETED, INCLUDING WELDING, THE MATERIAL SHOULD BE LEFT FOR 24 HOURS BEFORE ANY CLEANING IS CARRIED OUT

DAILY MAINTENANCE

- For light soiling wipe the walls with a damp cloth, using a neutral cleanser diluted to the manufacturer's instructions
- Never use an abrasive pad

ROUTINE AND PERIODIC MAINTENANCE

- If heavily soiled, especially with grease, wipe the walls with a damp cloth, using an alkaline cleanser diluted to the manufacturer's instructions
- Afterwards, rinse the walls using clean warm water and a small amount of neutralising agent such as acetic acid

STEAM CLEANING

The Polyclad range of wall and ceiling coverings are suitable for steam cleaning on a periodic basis.

