POLYFLOR™
COVERING THE WORLD

Camaro PUR

PRODUCT SPECIFICATION

KEY FEATURES

- Wood, parquet & stone designs
- Multiple plank & tile sizes
- Inlay accessories available
- Low VOC emissions
- Light commercial & residential interiors



PRODUCT FORMAT	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Wear Layer	ISO 24340 (EN 429)	0.30mm
Total Weight	ISO 23997 (EN 430)	3600g/m²
Finish		PUR

PLANK & TILE SIZES	Size	Shades	**Quantity** per Box	**Coverage** per Box/Roll
	Size Mix	1	36	3.62m²
	76.2mm x 228.6mm	2	192	3.34m²
	76.2mm x 457.2mm	3	96	3.34m²
Plank	101.6mm x 914.4mm	1	36	3.34m²
	152.4mm x 914.4mm	1	24	3.34m²
	152.4mm x 1219.2mm	1	18	3.34m²
	184.2mm x 1219.2mm	13	15	3.37m²
Tile	304.8mm x 304.8mm	1	36	3.34m²
	304.8mm x 609.6mm	7	18	3.34m²

PERFORMANCE REQUIREMENTS	Standard	Result
General Performance	ISO 10582 (EN 649)	Conforms
Use Area	ISO 10874 (EN 685)	23
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 ASTM D2047	Class DS R10 R10 SCOF ≥0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T

Reaction to Fire	EN 13501-1 ASTM E662 ASTM E648 AS ISO 9239.1	Class BfI-S1 <450 Pass Class 1 ≥ 8kW/m²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1 ASTM F970 ASTM F1914	<0.05mm* ≤0.005" @ 750psi ≤0.005"
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434) ASTM F2199	≤0.10% Pass
Underfloor Heating		Suitable, max 27ºC
Light Fastness	ISO 105-B02 (Method 3)	≥6
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets
*Average test value from current production.		

SUSTAINABILITY	**Standard**	**Result**
BRE Green Guide		A+ ENP 429
GreenTag	GreenRate™	Level A
Generic EPD	EN 15804	Available
Recyclable		100%*
Recycled Content	EN 17861	18%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001 SA 8000	Very good Approved factory

*Polyflor is a founding member of resilient flooring recycling schemes Recofloor and Resiloop. Recofloor accepts LVT. The newly formed Resiloop in Australia is currently only accepting LVT offcuts. See https://www.polyflor.com.au/resiloop for further information including collection locations. Polyflor is committed to supporting efforts to increase the proportion of vinyl flooring waste which is recycled locally & internationally.

ACOUSTIC PERFORMANCE	**Standard**	**Result**
Impact Sound Reduction	ISO 10140-3	2dB
Sound Transmission Coefficient	ASTM E90/492	STC 55
Impact Insulation Class	ASTM E90/492	IIC 39

MAINTENANCE PERFORMANCE	**Standard**	**Result**
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance
Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.		

BS EN 14041 EN 14041

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

Camaro

RANGE SHADES **30** Shades

SMALL PARQUET



2251 CAMBRIDGE PARQUET
76.2 x 228.6mm



2252 GEORGIAN PARQUET
76.2 x 228.6mm

LARGE PARQUET

Also available in **WOOD** (Plank Format)



LPQ2257 NAKED BLOND OAK
LARGE PARQUET
76.2 x 457.2mm



LPQ2253 WESTCHESTER OAK
LARGE PARQUET
76.2 x 457.2mm



LPQ2256 WATERSIDE OAK
LARGE PARQUET
76.2 x 457.2mm

WOOD COLLECTION



2202 NUT TREE 101.6 x 914.4mm



2247 SALVAGED TIMBER 76.2 / 101.6 / 152.4 x 914.4mm

With regard to colour printing, it is only possible to give a provisional representation of the product colour. For colour selection an original sample should be used, which we shall be pleased to supply free of charge. To replicate the natural material, the stone effect tiles may include variation in markings as part of their design.

WOOD COLLECTION



2233 SMOKE BRUSHED ELM 152.4 x 914.4mm



2232 NATURAL OAK 152.4 x 1219.2mm



PLK2257 NAKED BLOND OAK 184.2 x 1219.2mm



PLK2253 WESTCHESTER OAK 184.2 x 1219.2mm



PLK2256 WATERSIDE OAK 184.2 x 1219.2mm



2241 BIANCO OAK 184.2 x 1219.2mm



2254 ROSEDALE OAK 184.2 x 1219.2mm



2242 BOATHOUSE OAK 184.2 x 1219.2mm

Also available in **LARGE PARQUET**

This design intentionally features a strong pattern and/or colour variation to accurately replicate natural timber

This design features a micro bevel

WOOD COLLECTION



2258 FENLAND OAK 184.2 x 1219.2mm



2246 QUAYSIDE OAK 184.2 x 1219.2mm



2244 CASHMERE OAK 184.2 x 1219.2mm



2248 SIENNA OAK 184.2 x 1219.2mm



2259 ASTORIA OAK 184.2 x 1219.2mm




2249 WILD AMBER OAK 184.2 x 1219.2mm



2261 BAYSWATER OAK 184.2 x 1219.2mm

This design intentionally features a strong pattern and/or colour variation to accurately replicate natural timber

STONE COLLECTION



2339 ATLANTIC SLATE
304.8 x 304.8mm



2319 OCEAN SLATE
304.8 x 609.6mm



2347 SOHO CEMENT
304.8 x 609.6mm



2348 TRIBECA CEMENT
304.8 x 609.6mm



2332 WHITE METALSTONE
304.8 x 609.6mm



2341 ARCTIC SLATE
304.8 x 609.6mm



2342 BURNISHED CONCRETE
304.8 x 609.6mm



2349 GOLDSTONE MICRO TERRAZZO
304.8 x 609.6mm

With regard to colour printing, it is only possible to give a provisional representation of the product colour. For colour selection an original sample should be used, which we shall be pleased to supply free of charge. To replicate the natural material, the stone effect tiles may include variation in markings as part of their design.