


# Karri PUR

## PRODUCT SPECIFICATION

### KEY FEATURES

- A mix of modern and bold shades.
- Knot and grain detailing.
- Withstand years of family living.
- Heavy commercial applications & residential.



PRODUCT FORMAT	Standard	Result
Gauge	ISO 24346 (EN 428)	5.0mm
Wear Layer	ISO 24340 (EN 429)	0.70mm
Total Weight	ISO 23997 (EN 430)	8000g/m <sup>2</sup>
Finish		PUR

PLANK SIZE	Size	Shades	Quantity per Box	Coverage per Box/Roll
Plank	185mm x 1505mm	10	8	2.23m <sup>2</sup>

PERFORMANCE REQUIREMENTS	Standard	Result
General Performance	ISO 10582 (EN 649) ASTM F1700	Conforms Class III Type A+B
Use Area	ISO 10874 (EN 685)	23, 34, 43
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 Appendix D ASTM D2047	Class DS R10 R10 SCOF ≥0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T
Reaction to Fire	EN 13501-1 ASTM E662 ASTM E648 AS ISO 9239.1 CAN/ULC S102.2	Class Bfl-S1 <450 Pass Class 1 ≥ 8kW/m <sup>2</sup> FSV < 300; SDV < 500
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1 (EN 433) ASTM F970 ASTM F1914	≤0.10mm* ≤0.005" @ 750psi ≤0.005"

Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434) ASTM F2199	≤0.10% Pass
Flexibility	ASTM F137	1" - Pass
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

\*Average test value from current production.

SUSTAINABILITY	Standard	Result
BRE Green Guide		A+ - Generic
Recyclable		100%
Recycled Content		20%
Bio-PVC		Contains Bio-PVC
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Meets requirements
AgBB/ABG		Pass

ACOUSTIC PERFORMANCE	Standard	Result
Impact Sound Reduction	ISO 10140-3	8dB
Sound Transmission Coefficient	ASTM E90/492	STC 55
Impact Insulation Class	ASTM E90/492	IIC 46

MAINTENANCE PERFORMANCE	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance

Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.



# Karri PUR

RANGE SHADES

10 Shades

Plank Size : 185 x 1505mm



**7070** OPAL



**7071** DUNE



**7072** REEF



**7073** DESERT



**7074** KAKADU

Plank Size : 185 x 1505mm



**7075 GUMLEAF**



**7076 WATTLE**



**7077 SEASPRAY**



**7078 JACARANDA BLACKBUTT**



**7079 OUTBACK SPOTTED GUM**

**R10** All designs achieve R10, which is an ex-factory measure of slip resistance